

PRODUCT DETAILS

Product Code	1225-II -PL
Construction	Engineered Tongue and Groove
Pattern	Single Strip Plank
Top Layer Specie	European oak
Total Thickness	15mm
Finish	Hand-finished and fully protected with 4 layers of hard wax oil
Grade	Character, Nature, Select
Edge Profile	Micro-bebelled on two long sides only





ABALONE PLANKS

TECHNICAL CRITERIA

Wear Layer Thickness	4mm European oak
Backing	WBP European birch cross layer plywood
Width	180 mm; 220 mm; 240 mm
Length	Random lengths boards 40% between 600mm and 1990mm, and 60% between 2000mm and 2800mm.
Pack Size	Made to order
Certifications	FSC
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emissions	CARB Phase 2
Pentachlorophenol Emissions	< 5 ppm
Reaction to Fire Classification	Cfl-s1
Slip Testing	63/38 PTV (CEN/TS 15676:2007)

INSTALLATION METHODS

Connection System	Tongue & groove
UFH Suitability	Tested and compatible with underfloor heating system

IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer in accordance with the relevant national standard. Inspect all goods before fitting.

Do not cover a newly installed floor with non-breathable material. Trapped moisture can damage the surface, especially over underfloor heating.