

TECHNICAL DATA SHEET

PRODUCT DETAILS

Product Code	bronze
Construction	Engineered Tongue and Groove
Pattern	Single Strip Plank
Top Layer Specie	European oak (Quercus petraea)
Total Thickness	15mm
Finish	Hand-finished and fully protected by three layers of hard wax oil
Grade	Prime, Nature, Character
Edge Profile	Micro-beveled on all four sides

BRONZE



TECHNICAL CRITERIA

Wear Layer Thickness	4mm European oak
Backing	WBP European birch (Betula pendula) cross layer plywood
Width	180/220/240/260/300 mm
Length	Random lengths boards 40% between 600mm and 1990mm, and 60% between 2000mm and 2800mm.
Pack Size	Made to order

INSTALLATION METHODS

Connection System	Tongue & groove
-------------------	-----------------

IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer in accordance with the relevant national standard. Inspect all goods before fitting.

Do not cover a newly installed floor with non-breathable material. Trapped moisture can damage the surface, especially over underfloor heating.

219 Northfield Avenue, West Ealing, London, W13 9QU

Tel: +44 (0)20 8932 2176 | Email: info@3oak.co.uk

