

TECHNICAL DATA SHEET

PRODUCT DETAILS

Product Code	caramel
Construction	Engineered Tongue and Groove
Pattern	Single Strip Plank
Top Layer Specie	European oak (Quercus petraea)
Total Thickness	15mm
Finish	Hand-finished and fully protected by three layers of hard wax oil
Grade	Prime, Nature, Character
Edge Profile	Micro-beveled on all four sides

CARAMEL



TECHNICAL CRITERIA

Wear Layer Thickness	4mm European oak
Backing	WBP European birch (Betula pendula) cross layer plywood
Width	Made to measure
Length	Random lengths boards 40% between 600mm and 1990mm, and 60% between 2000mm and 2800mm.
Pack Size	Made to order

INSTALLATION METHODS

Connection System	Tongue & groove
-------------------	-----------------

IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer in accordance with the relevant national standard. Inspect all goods before fitting.

Do not cover a newly installed floor with non-breathable material. Trapped moisture can damage the surface, especially over underfloor heating.

219 Northfield Avenue, West Ealing, London, W13 9QU

Tel: +44 (0)20 8932 2176 | Email: info@3oak.co.uk

