

TECHNICAL DATA SHEET

PRODUCT DETAILS

Product Code	high-elms-herringbone
Construction	Engineered Tongue and Groove
Pattern	Herringbone Parquet
Top Layer Specie	Reclaimed Barn Oak (150+ years old)
Total Thickness	15mm
Finish	Hand-finished and fully protected with three layers of hard wax oil
Grade	Prime
Edge Profile	Micro-bevelled on all four sides



HIGH ELMS – HERRINGBONE



TECHNICAL CRITERIA

Wear Layer Thickness	4mm European oak
Backing	WBP European birch cross layer plywood
Width	160 mm; 180 mm; 220 mm
Length	Made to measure
Pack Size	Made to order

INSTALLATION METHODS

Connection System	Tongue & groove
UFH Suitability	Tested and compatible with underfloor heating system

IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer in accordance with the relevant national standard. Inspect all goods before fitting.

Do not cover a newly installed floor with non-breathable material. Trapped moisture can damage the surface, especially over underfloor heating.

219 Northfield Avenue, West Ealing, London, W13 9QU

Tel: +44 (0)20 8932 2176 | Email: info@3oak.co.uk

