

# TECHNICAL DATA SHEET

## PRODUCT DETAILS

|                  |                                                                     |
|------------------|---------------------------------------------------------------------|
| Product Code     | matt-nickel                                                         |
| Construction     | Engineered Tongue and Groove                                        |
| Pattern          | Herringbone Parquet                                                 |
| Top Layer Specie | European oak                                                        |
| Total Thickness  | 15mm                                                                |
| Finish           | Hand-finished and fully protected with three layers of hard wax oil |
| Grade            | Prime                                                               |
| Edge Profile     | Micro-bevelled on all four sides                                    |



## TECHNICAL CRITERIA

|                      |                                                                                        |
|----------------------|----------------------------------------------------------------------------------------|
| Wear Layer Thickness | 4mm European oak                                                                       |
| Backing              | WBP European birch cross layer plywood                                                 |
| Width                | 160 mm; 180 mm; 220 mm                                                                 |
| Length               | Random lengths boards 40% between 600mm and 1990mm, and 60% between 2000mm and 2800mm. |
| Pack Size            | Made to order                                                                          |

## INSTALLATION METHODS

|                   |                                                      |
|-------------------|------------------------------------------------------|
| Connection System | Tongue & groove                                      |
| UFH Suitability   | Tested and compatible with underfloor heating system |

## IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer in accordance with the relevant national standard. Inspect all goods before fitting.

Do not cover a newly installed floor with non-breathable material. Trapped moisture can damage the surface, especially over underfloor heating.

219 Northfield Avenue, West Ealing, London, W13 9QU

Tel: +44 (0)20 8932 2176 | Email: [info@3oak.co.uk](mailto:info@3oak.co.uk)

© 2026 3 OAK. All information was correct at the time of publication; the company reserves the right to change this specification at any time without notice. Photographs are illustrative only and may vary slightly

