TECHNICAL DATA SHEET

Engineered Herringbone · Signature Herringbone Parquet

SILVER WASHED PARQUET

PRODUCT DETAILS

Product Code	SilverW-HB
Construction	Engineered Tongue and Groove
Pattern	Herringbone Parquet
Top Layer Specie	European oak
Total Thickness	15mm
Finish	Hand-finished and fully protected with three layers of natural, eco-friendly coating
Grade	Character, Nature, Select
Edge Profile	Micro-bevelled on all four sides

4 PLUS PROTECT SYSTEM®

UK HAND FINISHED IN

FSC FORESTS FOR ALL FOREVER™

ENGINEERED & MANUFACTURED BY 3 OAK

TECHNICAL CRITERIA

Wear Layer Thickness	4mm European oak
Backing	WBP European birch plywood or 3 Oak™construction featuring European oak
Width	160 mm; 180 mm; 220 mm
Length	70x350mm, 90x400mm, 100x500mm, 120x600mm
Pack Size	Made to order

INSTALLATION METHODS

Connection System	Tongue & groove
UFH Suitability	Tested and compatible with underfloor heating system

IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer in accordance with the relevant national standard. Inspect all goods before fitting.

Do not cover a newly installed floor with non-breathable material. Trapped moisture can damage the surface, especially over underfloor heating.

219 Northfield Avenue, West Ealing, London, W13 9QU

Tel: +44 (0)20 8932 2176 | Email: info@3oak.co.uk

3 OAK

© 2026 3 OAK. All information was correct at the time of publication; the company reserves the right to change this specification at any time without notice. Photographs are illustrative only and may vary slightly