TECHNICAL DATA SHEET

PRODUCT DETAILS

TRUFFLE OAK PLANK

Product Code	1183-PL
Construction	Engineered Tongue and Groove
Pattern	Single Strip Plank
Top Layer Specie	European oak
Total Thickness	15mm
Finish	Hand-finished and fully protected by 4 layers of eco-friendly lacquer
Grade	Character
Edge Profile	Micro-bebelled on two long sides only



4 PLUS PROTECT SYSTEM®

UK HAND FINISHED IN

FSC FORESTS FOR ALL FOREVER™

ENGINEERED & MANUFACTURED BY 3OAK

TECHNICAL CRITERIA

Wear Layer Thickness	4mm European oak
Backing	WBP European birch cross layer plywood
Width	180 mm
Length	Random lengths boards 30% between 1000mm and 1990mm, and 70% between 2000mm and 2800mm.
Pack Size	Made to order

INSTALLATION METHODS

Connection System	Tongue & groove
UFH Suitability	Tested and compatible with underfloor heating system

IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer in accordance with the relevant national standard. Inspect all goods before fitting.

Do not cover a newly installed floor with non-breathable material. Trapped moisture can damage the surface, especially over underfloor heating.

219 Northfield Avenue, West Ealing, London, W13 9QU

Tel: +44 (0)20 8932 2176 | Email: info@3oak.co.uk

3OAK

© 2026 3 OAK. All information was correct at the time of publication; the company reserves the right to change this specification at any time without notice. Photographs are illustrative only and may vary slightly