

# TECHNICAL DATA SHEET

Engineered Planks · Artisan Bespoke Planks

## PRODUCT DETAILS

|                  |                                  |
|------------------|----------------------------------|
| Product Code     | UV113HB                          |
| Construction     | Engineered Tongue and Groove     |
| Pattern          | Herringbone Parquet              |
| Top Layer Specie | European oak ( Quercus petraea ) |
| Total Thickness  | 15mm                             |
| Finish           | UV Oiled                         |
| Grade            | Character                        |
| Edge Profile     | Micro-beveled on all four sides  |

UV113HB



## TECHNICAL CRITERIA

|                      |                                                           |
|----------------------|-----------------------------------------------------------|
| Wear Layer Thickness | 4mm European oak                                          |
| Backing              | WBP European birch ( Betula pendula ) cross layer plywood |
| Pack Size            | Made to order                                             |

## INSTALLATION METHODS

|                   |                 |
|-------------------|-----------------|
| Connection System | Tongue & groove |
|-------------------|-----------------|

## IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer in accordance with the relevant national standard. Inspect all goods before fitting.

Do not cover a newly installed floor with non-breathable material. Trapped moisture can damage the surface, especially over underfloor heating.

219 Northfield Avenue, West Ealing, London, W13 9QU

Tel: +44 (0)20 8932 2176 | Email: info@3oak.co.uk

